

Self Bunded Fuel Storage Tank Specifications

- Heavy duty design for arduous on site conditions.
- Fabricated from high grade mild steel and self bundled for static storage.
- Bunded outer tank capacity 110% of volume and easily removable inner tank for maintenance and cleaning.
- Designed for economical storage and transportation in containers and truck beds.
- Fully baffled to prevent fuel surge during transportation.
- Inner and outer tanks sand blasted to SA2.5 and one coat of epoxy zinc rich primer and three coats of epoxy high build polyurethane surface paint.
- Compliant with pollution prevention guidelines (PPG2/PPG26), Australian Standards AS1692 and AS1940 and approved to UL 142, ULCS 601 and UN 31A for diesel.
- All tanks can be utilised as external fuel cells and are fitted with 2 x suction and 2 x return points.

Size	Safe Fill Level (Litres)	Length (mm)	Width (mm)	Height (mm)	Empty Weight (kg)	Full Weight (kg)
BFA2000	1800	2550	1050	1300	850	2650
BFA4500	4100	3000	2000	1300	1450	5800
BFA6300	5950	3870	2000	1300	1850	8100
BFA10000	9000	6060	2440	1300	4500	13000



T 1300 57 9990 F 07 3259 8626
service@bulkfuel.com.au
www.bulkfuel.com.au