



Specifications and Equipment

Vacuum Truck 3000L Hi CFM



**Truck manufacturer : ISUZU
Model: FSR 850**



**Vac unit Manufacturer: Ring
O Matic
Model: 3000L Hi CFM**



Our range of Hi CFM Hydro vac excavators are designed for smaller volume applications. They are a cost effective way to hydro excavate in suburban areas and tight job sites. Don't be mistaken these smaller units still pack a punch and are the work-horse of the vacuum truck industry.

Specifications

- Weight 8.5tonne (empty)
- All vehicles are fitted with first aid kit, oil spill kit, sharp kit, sediment socks, and all required PPE
- 300 CFM Gardner Denver Blower
- Cat Pressure Sensitive Regulating Unloader Valve
- Pressurized Discharge with 2" Pressure Relief Valve
- Large Silencer Muffler for Noise Abatement
- Diesel Tank approx. 100 Liter
- Spoils tank approx. 3000 Liter
- Fresh Water Tanks with 1½ " Drain Valve, approx. 2000 Litre
- Low Water – Pump Shut-off Switch
- 1" Fresh Water Filter with #40 Mesh Screen
- 4" Brass Gate Valve for Spoils Tank Discharge • Pressurized Discharge
- 5 Micron Washable Dustcotech Filters x 4
- Door Closure Cammed for Using Single Handle, Moving 6 Dead Bolts into Lock Position
- Hydraulic Door Cylinder Internally Ported for Safety In The Event of Hose Failure
- Multi Stage Lift Rams, Valve and Steel Reservoir
- Lockable Hose Reel w/ 30 Meters of 3/8" HP Hose & Flexible Spray Wand with Nozzle Protector
- 2 x 6 Meters 4" Suction Hose w/ Ball & Socket Ends (or 4" if required)
- 2 x Lances with Trigger Guns & Turbo Nozzles
- Work lights fitted for night work
- Orange hazard lights



Specifications and Equipment

Vacuum Truck 6000L Vac Extreme



Truck manufacturer : VOLVO
Model: FE 300



Vac unit Manufacturer: Ring
O Matic
Model: 6000L Vac Extreme



Our range of Vac Extreme Hydro Excavators were designed to take into consideration the extra volume of material to be excavated more quickly. It is a cost effective solution for more difficult jobs. These machines can run up to a 6" hose but work most efficiently with a 5" hose.

Specifications

- All vehicles are fitted with first aid kit, oil spill kit, sharp kit, sediment socks, and all required PPE
- Cat 83 HP Diesel Engine
- 1750 CFM Gardner Denver Blower
- Comet High Pressure Water pump 6.0 GPM @ 4000 PSI Water Flow
- Cat Pressure Sensitive Regulating Unloader Valve
- Pressurized Discharge with 2" Pressure Relief Valve
- Large Silencer Muffler for Noise Abatement
- Diesel Tank approx. 100 Litre
- Spoils tank approx. 6000 Litre
- Fresh Water Tanks with 1½ " Drain Valve, approx. 2000 Litre
- Low Water – Pump Shut-off Switch
- 1" Fresh Water Filter with #40 Mesh Screen
- 6" Brass Gate Valve for Spoils Tank Discharge • Pressurized Discharge
- 5 Micron Washable Dustcotech Filters x 7
- Hydraulic Full Opening Rear Door
- Door Closure Cammed for Using Single Handle, Moving 6 Dead Bolts into Lock Position
- Hydraulic Door Cylinder Internally Ported for Safety In The Event of Hose Failure
- Multi Stage Lift Rams, Valve and Steel Reservoir
- Lockable Hose Reel w/ 30 Meters of 3/8" HP Hose & Flexible Spray Wand with Nozzle Protector
- 2 x 6 Meters 5" Suction Hose w/ Ball & Socket Ends (or 4" if required)
- 2 x Lances with Trigger Guns & Turbo Nozzles
- Remote control boom
- Work lights fitted for night work
- Orange hazard lights