AUCHVI **Construction Equipment Australia**

Unit 4/5 Graham St Underwood, Qld, 4119 P: 07 3208 7772 W: www.yuchai.com.au

YC15-8 HYDRAULIC EXCAVATOR

Machine Weight:

Power:

Volume of Bucket:

1625kg

14.7kW/2200rpm

0.05m3







Comfortable operating position with large operator seat and pilot



Designed for Australian conditions with large radiator & oil cooler with highly efficient air flow design







High strength boom and dipper arm with serviceable pins and bushes



DIMENSIONS





Α	Maximum length of Transportation	3670mm
В	Machine Height	2245mm
С	Overall width	990mm
D	Width of track	230mm
E	Platform Tail Turning Radius	1175mm
F	Length of track	1419mm
G	Sprocket to idler centres	1045mm
Н	Between undercarriage and ground	188mm
1	Between boom and ground	1065mm
J	Width of Platform	990mm
L	Between platform and ground	453mm



RANGE OF OPERATION

Α	Maximum Digging Height	2910mm
В	Maximum Dumping Height	2050mm
С	Maximum Digging Depth	1800mm
D	Maximum Digging Radius	3520mm
Е	Maximum Height Digging Radius	2650mm
F	Minimum Turning Radius	1694mm

■ PERFORMANCE AND SPECIFICATION

Engine Model	14.7kW@2200rpm Kubota
Operation hydraulic pressure	16MPa
Pump	2 x 17.6 + 6.6 l/m
Maximum Digging Force	7.2kN
Gradeability	30°
Pressure to the Ground	27.7kPa
Walking Speed	1.68/2.98 km/h
Maximum Hauling Force	14.65kN
Swing Speed of Platform	12rpm

