

MP70 Single Direction Vibratory Plates



This plate proves that performance is valuable

With a powerful Wacker Neuson petrol engine, low weight, compact dimensions and low-maintenance design, the MP70 Vibratory Plate is ideal for the compaction of sand, crushed rock, granular materials and segmental brick paving.

- Compact design with centrally mounted, fully enclosed exciter for an even spread of compaction force over the whole base plate.
- Sturdy 4-stroke petrol engine with recoil starter is isolated from vibration by rubber dampers.
- Vibration isolated reversible handle with throttle control for ease of operation and reduced operator fatigue.
- Conveniently placed lifting handles, and a central lifting point for safe and easy handling.
- Low maintenance design.

MP70 Standard Package includes operator's manual and parts book.

Item No. 0630243



Technical specifications

Operating data

Operating weight (without fuel)	76 kg
Centrifugal force	15 kN
Base plate size (w × I)	460 x 610 mm
Advance travel max. (depending on soil)	30 m/min
Surface capacity max. (depending on soil)	830 m²/h
Engine / Motor	
Engine / Motor type	Air-cooled, single cylinder, 4-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson
Engine / Motor	WN6
Displacement	179 cm ³
Engine performance (max.)	4.2 kW
at rpm	3,600 rpm
Fuel consumption	1.27 l/h
Tank capacity	3.61

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2017 Wacker Neuson SE.