

HOPPER

Width	1.83m (6')
Length	4.1m (13' 5")
Max volume (with extensions)	10m ³ (13yd ³)

FEEDER BELT

Width	1050mm (42")
Type	Plain belt
Control	Variable speed

VIBRATING GRID

Length	3.70m (12' 1")	
Width	2.0m (6' 7")	
Screen decks	Bofor Bars	Finger Tines
	Punch Plate	Mesh

TIPPING GRID

Width	2.20m (7' 2")	
Length	4.95m (16' 2")	
Screen decks	Bofor bar	Mesh

MAIN BELT

Width	1050mm (42")
Control	Variable speed
Max discharge height	3.97 (13' 1")

TRACKS

Width	300mm
Speed	1km/h

POWERPACK

Diesel tank	160L (35 gallon/42 US gallon)
Hydraulic tank	345L (76 gallon/91 US gallon)

**OPTIONS**

1. Radio remote tipping grid
2. Two-deck vibrating grid
3. Dust cover over main belt
5. Radio remote control
6. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
Tier 4F - JCB444 EcoMAX - 55Kw - USA
Stage V - T.Deutz 2.9L4 - 50Kw - EU
7. Overband Magnet
8. Flared Extensions
9. Straight Extensions
10. Mulching Drum Kit

PERFORMANCE

Max feed size	200mm
Capacity	up to 700 tph

WORKING DIMENSIONS

Length	11.68 (38' 0")
Width	2.25m (7' 4")
Height	4.15 (13' 6")

TRANSPORT DIMENSIONS

Length	11.90m (38' 11")
Width	2.25m (7' 4")
Height	2.50m (8' 4")

GENERAL FTR 100

Weight			
Open Feed	12,700 kg	13.9 US TON	27998 lbs
Tipping grid	14,400 kg	15.9 US TON	31746 lbs
Vibrating grid	17,200 kg	18.9 US TON	37919 lbs

ANACONDA®
A McLanahan Company

Copyright 2014 by Anaconda Equipment International. All rights reserved
This document or any part thereof must not be reproduced without the permission of Anaconda