

HOPPER

Width	1.83m (6')
Length	4.1m (13' 5")
Max volume (with extensions)	10m ³ (13yd ³)

FEEDER BELT

Width	1050mm (42")
Type	Plain belt
Control	Variable speed

VIBRATING GRID

Length	3.70m (12' 1")	
Width	2.0m (6' 7")	
Screen decks	Bofor Bars	Finger Tines
	Punch Plate	Mesh

TIPPING GRID

Width			2.20m (7' 2")
Length			4.95m (16' 2")
Screen decks	Bofor bar	Mesh	

MAIN BELT

Width	1050mm (42")
Control	Variable speed
Min discharge height	4.06m (13' 3")
Max discharge height	6.35m (20' 8")

TRACKS

Width	300mm
Speed	1km/h

POWERPACK

Diesel tank	160L (35 gallon/42 US gallon)
Hydraulic tank	345L (76 gallon/91 US gallon)

**OPTIONS**

1. Radio remote tipping grid
2. Two-deck vibrating grid
3. Dust cover over main belt
5. Radio remote control
6. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
Tier 4F - JCB444 EcoMAX - 55Kw - USA
Stage V - T.Deutz 2.9L4 - 50Kw - EU
7. Overband Magnet
8. Flared Extensions
9. Straight Extensions
10. Mulching Drum Kit

PERFORMANCE

Max feed size	200mm
Capacity	up to 700 tph

WORKING DIMENSIONS

Length	17.30m (56' 11")
Width	2.25m (7' 4")
Height	6.58m (21' 6")

TRANSPORT DIMENSIONS

Length	11.90m (38' 11")
Width	2.25m (7' 4")
Height	2.50m (8' 4")

GENERAL

Weight			
Open Feed	13,300 kg	14.7 US TON	29400 lbs
Tipping grid	15,000 kg	16.5 US TON	33100 lbs
Vibrating grid	17,800 kg	19.6 US TON	39200 lbs

ANACONDA®
A McLanahan Company

Copyright 2014 by Anaconda Equipment International. All rights reserved

This document or any part thereof must not be reproduced without the permission of Anaconda