

HOPPER

Width	1.83m (6')
Length	4.1m (13' 5")
Max volume	13m ³ (17yd ³)

(with both flared and straight extensions)

FEEDER BELT

Width	1050mm (42")
Type	Plain belt
Control	Variable speed

VIBRATING GRID

Length	3.70m (12' 1")	
Width	2.0m (6' 7")	
Screen decks	Bofor Bars	Finger Tines
	Punch Plate	Mesh

TIPPING GRID

Width	2.20m (7' 2")	
Length	4.95m (16' 2")	
Screen decks	Bofor bar	Mesh

MAIN BELT

Width	1050mm (42")
Control	Variable speed
Min discharge height	6.08m (19' 9")
Max discharge height	8.77m (28' 8")

TRACKS

Width	400mm
Speed	1km/h

POWERPACK

Diesel tank	160L (35 gallon/42 US gallon)
Hydraulic tank	345L (76 gallon/91 US gallon)

**OPTIONS**

1. Radio remote tipping grid
2. Two-deck vibrating grid
3. Dust cover over main belt
5. Radio remote control
6. Overband Magnet
7. Flared Feeder Extensions
8. Straight Feeder Extensions
9. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
Tier 4F - JCB444 EcoMAX - 55Kw - USA
Stage V - T.Deutz 2.9L4 - 50Kw - EU
10. Mulching Drum Kit

PERFORMANCE

Max feed size	200mm
Capacity	up to 700 tph

WORKING DIMENSIONS

Length	22.49m (73' 8")
Width	2.55m (8' 3")
Height	8.97m (29' 4")

TRANSPORT DIMENSIONS

Length	16.13m (52' 9")
Width	2.55m (8' 3")
Height	2.58m (8' 5")

GENERAL

Weight			
Open Feed	14485 kg	15.9 US TON	31933 lbs
Tipping grid	17000 kg	18.7 US TON	37478 lbs
Vibrating grid	18985kg	20.9 US TON	41854 lbs

ANACONDA[®]
A McLanahan Company

Copyright 2014 by Anaconda Equipment International. All rights reserved

This document or any part thereof must not be reproduced without the permission of Anaconda